

MOTIVE POWER TRACTION BATTERY



SPEC Sheet for V Series Produced in Thailand

GS YUASA TRACTION BATTERIES Made in Thailand

(JIS TYPE/2V)

MODEL	Nominal Capacity (Ah/5HR)	Dimensions (mm)				Acid (L)	Weight with Acid (kg)	Q'ty per Pallet
		(L)	(W)	(h)	(H)			
VSD3A	170	60	158	395	426	1.7	9.5	96
VSD4B	225	94	158	395	426	3.2	13.0	66
VSD5A	265	94	158	395	426	3.2	15.0	66
VSD6	335	128	158	395	426	4.2	19.0	42
VSD7C	340	144	158	395	426	5.5	19.5	42
VSD8AC	435	144	158	395	426	4.6	23.0	42
VSD9AC	475	161	158	395	426	5.1	25.5	36
VSD10AC	540	177	158	395	426	5.6	28.5	30
VSD12AC	645	206	158	395	426	6.4	34.0	24
VSF3A	210	60	158	490	521	2.1	12.0	96
VSF270	270	72	158	490	521	2.8	15.0	84
VSF3C	225	90	158	490	521	3.6	14.5	66
VSF4	290	90	158	490	521	3.5	17.0	66
VSF340	340	90	158	490	521	3.3	18.5	66
VSF5A	350	99	158	490	521	3.8	19.5	60
VSF6A	420	109	158	490	521	4.1	22.5	54
VSF8	545	144	158	490	521	6.6	30.5	42
○ VSF10A	700	177	158	490	521	7.7	38.0	30
VSI2C	150	46	158	519	550	1.6	10.0	126
VSI3A	240	60	158	519	550	2.3	13.5	96
VSI3C	270	72	158	519	550	2.8	15.5	84
VSI4C	350	90	158	519	550	3.7	19.0	66
VSI6C	435	109	158	519	550	4.2	24.5	54
VSI7C	510	126	158	519	550	4.9	28.0	48
VSI8C	580	142	158	519	550	5.5	32.0	42
VSI9C	655	158	158	519	550	6.2	36.0	36
○ VSI9D	715	171	158	519	550	6.7	40.0	30
○ VSI11C	865	206	158	519	550	8.1	47.5	24
VCH3C	300	60	158	700	731	3.0	18.0	78
VCH4C	400	78	158	700	731	4.1	23.0	60
VCH5C	490	94	158	700	731	5.1	28.0	48
VCH6C	580	109	158	700	731	5.9	33.0	42
VCH7C	680	126	158	700	731	6.9	38.0	36
○ VCH8C	770	142	158	700	731	7.7	43.5	30
○ VCH9C	870	158	158	700	731	8.7	48.5	30
○ VCH10C	950	171	158	700	731	9.3	53.0	24
VGD485	485	144	158	410	441	5.1	27.5	42
VGD545	545	161	158	410	441	5.7	30.5	36
VGD565	565	177	158	410	441	6.6	32.0	30
VGD600	600	177	158	410	441	6.5	33.5	30
○ VGD700	700	206	158	410	441	7.4	40.0	24
VGE245	245	75	158	447	478	2.6	14.0	78
VGE305	305	90	158	447	478	3.5	17.5	66
VGI370	370	90	158	519	550	4.1	21.0	66
VGI470	470	109	158	519	550	5.0	25.5	54
VGI565	565	128	158	519	550	5.7	32.0	48
VGI645	645	148	158	519	550	6.8	36.5	42
VGI725	725	161	158	519	550	7.3	40.0	36
VGF220	220	60	158	490	521	2.5	12.5	96
VGF445	445	109	158	490	521	4.8	23.5	54
VGF530	530	128	158	490	521	5.4	29.5	48
VGF730	730	177	158	490	521	6.5	41.0	30
○ VSF3AS	210	60	158	490	521	2.1	12.0	96

(BS TYPE/2V)

Model	Nominal Capacity (Ah/5HR)	(L)	(W)	(h)	(H)	Acid (L)	Weight with Acid (kg)	Q'ty per Pallet
VGL300H	300	60	158	609	640	2.4	17.0	78
VGL400H	400	78	158	609	640	3.5	22.0	66

○ : DOUBLE POLE

(DIN TYPE/2V)

MODEL	Nominal Capacity (Ah/5HR)	Dimensions (mm)				Acid (L)	Weight with Acid (kg)	Q'ty per Pallet
		(L)	(W)	(h)	(H)			
2DCJ230A (2PzS230)	230	47	198	545	575	2.3	14.0	95
3DCJ345A (3PzS345)	345	65	198	545	575	3.3	19.5	65
4DCJ460A (4PzS460)	460	83	198	545	575	4.3	26.5	50
5DCJ575A (5PzS575)	575	101	198	545	575	5.2	32.5	40
2DCM250A (2PzS250)	250	47	198	575	605	2.7	14.5	95
3DCM375A (3PzS375)	375	65	198	575	605	3.9	21.0	65
4DCM500A (4PzS500)	500	83	198	575	605	5.0	27.5	50
5DCM625A (5PzS625)	625	101	198	575	605	6.2	33.5	40
6DCM750A (6PzS750)	750	119	198	575	605	7.3	40.0	35
2DCP280A (2PzS280)	280	47	198	685	715	2.9	18.0	80
3DCP420A (3PzS420)	420	65	198	685	715	4.5	26.0	50
4DCP560A (4PzS560)	560	83	198	685	715	5.7	33.0	40
5DCP700A (5PzS700)	700	101	198	685	715	7.2	41.0	30
2DCS310A (2PzS310)	310	47	198	720	750	3.0	18.5	80
3DCS465A (3PzS465)	465	65	198	720	750	4.5	26.2	50
4DCS620A (4PzS620)	620	83	198	720	750	6.0	34.5	40
5DCS775A (5PzS775)	775	101	198	720	750	7.4	42.1	30
6DCS930A (6PzS930)	930	119	198	720	750	8.7	51.0	30
2DCJ230 (2PzS230)	230	47	198	545	575	2.3	14.0	95
3DCJ345 (3PzS345)	345	65	198	545	575	3.3	19.5	65
4DCJ460 (4PzS460)	460	83	198	545	575	4.3	26.5	50
5DCJ575 (5PzS575)	575	101	198	545	575	5.2	32.5	40
2DCM250 (2PzS250)	250	47	198	575	605	2.7	14.5	95
3DCM375 (3PzS375)	375	65	198	575	605	3.9	21.0	65
4DCM500 (4PzS500)	500	83	198	575	605	5.0	27.5	50
5DCM625 (5PzS625)	625	101	198	575	605	6.2	33.5	40
6DCM750 (6PzS750)	750	118.5	198	575	605	7.3	40.0	35
2DCP280 (2PzS280)	280	47	198	685	715	2.9	18.0	80
3DCP420 (3PzS420)	420	65	198	685	715	4.5	26.0	50
4DCP560 (4PzS560)	560	83	198	685	715	5.7	33.0	40
5DCP700 (5PzS700)	700	101	198	685	715	7.2	41.0	30
2DCS310 (2PzS310)	310	47	198	720	750	3.0	18.5	80
3DCS465 (3PzS465)	465	65	198	720	750	4.5	26.2	50
4DCS620 (4PzS620)	620	83	198	720	750	6.0	34.5	40
5DCS775 (5PzS775)	775	101	198	720	750	7.4	42.1	30
6DCS930 (6PzS930)	930	119	198	720	750	8.9	51.0	30

Welding type

Bolt on terminal